

TENAX TORPEDO

Extruded net

TENAX TORPEDO is a extruded net which grants complete shading decreasing wind effect by mobile wings that allow air to pass through. The word “work in progress” on the reflective band applied on the central strip.

Application:

Ideal for urban fencing, windy areas, construction sites where privacy is required.

PHYSICAL CHARACTERISTICS	TEST METHOD	UNIT	TORPEDO	NOTES
POLYMER TYPE			POLYETHYLENE	-
COLOUR			ORANGE - GREEN	-
PACKAGING			PE BAG	-

DIMENSIONAL CHARACTERISTICS	TEST METHOD	UNIT	TORPEDO	NOTES
UNIT WEIGHT		g/m ²	340.0	-
ROLL WIDTH		m	1.8	-
ROLL LENGTH		m	30.0	-
COVERED AREA		m ²	54.0	-
ROLL DIAMETER		m	0.21	-
ROLL VOLUME		m ³	0.08	-
ROLL WEIGHT		Kg	21.3	-





Just Indicating

The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values. Tenax nets are thermoplastic products subjected to shrinkage. MD: longitudinal direction. TD: transversal direction.



Tenax Spa Quality System has been assessed and registered in agreement with ISO:9001:2008 by SGS Italy and SGS UK.

The TENAX Laboratory has been created in 1980 and has been continuously improved with the purpose of assuring unequalled technical development of the products and accurate Quality Control. The TENAX Laboratory can perform mechanical, hydraulic and durability tests, according to the most important international standards like ISO, CEN, ASTM, DIN, BSI, UNI.



TENAX SpA
Via dell'Industria, 3
23897 Viganò (LC)
Tel. +39 039.9219300
Fax +39 039.9219290
customer.service@tenax.net